

Certificate of Conformance to Requirements for Welding Electrode

Product Type: Fabshield 23

Classification: E71T-14

Specifications: AWS A5.20/A5.20M; ASME SFA 5.20

Diameter Tested: 1/16"

Date Tested: 9/11/2020

Date Generated: 10/28/2020

This is to certify that the product named above and supplied on the referenced order number is of the same classification, manufacturing process, and material requirements as the material which was used for the test that was concluded on the date shown, the results of which are shown below. All tests required by the specifications shown for classification were performed at that time and the material tested met all requirements. It was manufactured and supplied by the Quality System Program of Hobart Brothers, which meets the requirements of ISO 9001, ANSI/AWS A5.01, and other specification and Military requirements, as applicable. This document supplies actual test results of non-specific inspection in conformance with the requirements of EN 10204, type 2.2 certification.

THE STEEL USED IN THIS LOT OF MATERIAL WAS MELTED AND MANUFACTURED IN THE U.S.A.

Test Settings

	lest Settings																									
Shielding Medium		Amps / Polarity			Volts WFS in/min(m/min)				ESO in(mm)				Preheat F(C)				ı	Interpass F(C)				Travel Speed in/min(cm/min)				
Self-Shielded		230 / DCEN		EN	20		110 (2	.8)	3/4 (19)				Room Temp					300(149)				8 (20.3)				
Mechanical Properties - Tensile																										
Shielding Medium		R	ef. No		Testin	g Conc	ditions		Ult. Tensile Strength psi (MPa)						Yield Strength p				ı psi (MPa)				Elong.% in 2"			
Self-	F	E1235	5	Aged	48 Hrs	220F		84,000 (581)					NA							NA						
Ref.No. Radiographic Inspection					Fillet Weld Test														\Box							
PE1235	ms			Horizontal :				Overhead :					:	Conforms				Vertical : Conforms						s		
Longitudinal Bend Test PE1235 : CONFORMS																										
	Chemical Analysis																									
Shielding M	Shielding Medium / Ref. No		Mn	Р	S	Si	Cu	Cr	V	Ni	Мо	Al	Ti	Nb	Со	вМ	/ Sn	Fe	Sb	N	Mg	Zn	Ве	Sb	As	
Self-Shielde	0.41	1.16	0.009	0.005	0.23	0.01	0.02	< .01	0.01	0.01	2.50				Г											

Dave Thomas, Quality Assurance Rep.

Certification and Limited Warranty - Data for the above supplied product are those obtained when welded and tested in accordance with the above specification. All tests for the above classification were satisfied. Other tests and procedures may produce different results.