

Certificate of Conformance to Requirements for Welding Electrode

Product Type: Fabshield 7027

Classification: E70T-7

Specifications: AWS A5.20/A5.20M; ASME SFA 5.20

 Diameter Tested:
 3/32"

 Date Tested:
 12/5/2024

 Date Generated:
 1/7/2025

This is to certify that the product named above and supplied on the referenced order number is of the same classification, manufacturing process, and material requirements as the material which was used for the test that was concluded on the date shown, the results of which are shown below. All tests required by the specifications shown for classification were performed at that time and the material tested met all requirements. It was manufactured and supplied by the Quality System Program of Hobart Brothers, which meets the requirements of ISO 9001, ANSI/AWS A5.01, and other specification and Military requirements, as applicable. This document supplies actual test results of non-specific inspection in conformance with the requirements of EN 10204, type 2.2 certification.

THE STEEL USED IN THIS LOT OF MATERIAL WAS MELTED AND MANUFACTURED IN THE U.S.A.

Test Settings

lest settings																								
Amps	s / Pola	rity	Volts	in/m	WFS nin(m/n	nin)	ESO in(mm)				Preheat F(C)					Interpass F(C)					Travel Speed in/min(cm/min)			
400	/ DCE	:N	26 200 (5.1))	1	.25 (3	2)	П	Room Temp					300(149)				П	8 (20.3)			
Mechanical Properties - Tensile																								
Shielding Medium Ref. No.			Testing Conditions				Ult. Tensile Strength psi (MPa)					Yield Strength					psi (MPa)				Elong.% in 2"			
N/A PE9259				Aged 48 Hrs 220F				84,000 (576)					59,000 (410)					10)				24		
Ref.No. Radiographic Inspection							Fillet Weld Test																	
PE9259 Conforms				Horizontal : Co				ns Overhead					:					Vertical :						
Chemical Analysis																								
С	Mn	Р	S	Si	Cu	Cr	V	Ni	Мо	Al	Ti	Nb	Со	В	w s	Sn F	e	Sb	N	Mg	Zn	Ве	Sb	As
0.24	0.31	0.009	0.002	0.07	0.03	0.04	< .01	0.02	< .01	1.26				П										
	R P P P P P P P P P P P P P P P P P P P	Ref. No. PE9259 phic Inspection nforms C Mn	Ref. No. PE9259 phic Inspection Informs C Mn P	400 / DCEN 26 Me	A00 / DCEN 26 2	Amps / Polarity	Amps / Polarity	Amps / Polarity	Amps / Polarity Volts in/min(m/min) ESO in(r 400 / DCEN 26 200 (5.1) 1.25 (3	Amps / Polarity	Amps / Polarity	Amps / Polarity	Amps / Polarity											

James a Omenof

James A. Owens, Q.A. Specialist

Certification and Limited Warranty - Data for the above supplied product are those obtained when welded and tested in accordance with the above specification. All tests for the above classification were satisfied. Other tests and procedures may produce different results.