

Certificate of Conformance to Requirements for Welding Electrode

Product Type:	PIPEMASTER 70
Classification:	E7010-P1
Specifications:	AWS A5.5/A5.5M; ASME SFA 5.5
Diameter Tested:	5/32"; 3/16"
Date Tested:	8/12/2024
Date Generated:	9/30/2024

This is to certify that the product named above and supplied on the referenced order number is of the same classification, manufacturing process, and material requirements as the material which was used for the test that was concluded on the date shown, the results of which are shown below. All tests required by the specifications shown for classification were performed at that time and the material tested met all requirements. It was manufactured and supplied by the Quality System Program of Hobart Brothers, which meets the requirements of ISO 9001, ANSI/AWS A5.01, and other specification and Military requirements, as applicable. This document supplies actual test results of non-specific inspection in conformance with the requirements of EN 10204, type 2.2 certification.

MADE IN THE U.S. OF U.S. AND IMPORTED MATERIALS.

							Те	st Sett	ings																		
Size		Polarity						Am	ips		Volts				Γ	Preheat F(C)						Interpass F(C)					
3/16X14 in		DCEP						16	60	26				250F ()						250F ()							
5/32X14 in		DCEP					15	50	27				225F ()					250F ()									
					ľ	Mechai	nical	Prope	rties -	Tensil	e										<u> </u>						
Size / Polarity	Ref. No.	. Testing Conditions				Ult. Tensile Strength psi(M					/IPa) Yield Strength psi						si(MPa) E						Elong.% in 2"				
3/16X14 in / DCEP	PE8368	Aged 48 Hrs 220F				79,000 (543)					64,000 (444					14)					26						
5/32X14 in / DCEP	PE8496	Age	Aged 48 Hrs 220F				80,000 (553)					64,000 (439)										24					
					्रा	Mecha	nical	Prope	rties -	Impac	t																
Size / Polarity	Ref. No.	Test	Testing Conditions				Temp	. F(C)		Individuals ft.lb.(J)					Average ft.lb.(J)					Туре							
3/16X14 in / DCEP	PE8368	1	As Welded				F (-2	29 C)		58,73,	58,73,46 (79,99,62)				59 (80)					Charpy-V-Notch							
5/32X14 in / DCEP	PE8496		As Welded				F (-2	29 C) 53,56			6,53 (72,76,72)				54 (73)				Charpy-V-Notch								
Size / Polarity	Ref. No.	F	Radiogr	aph			Fillet Weld Test																				
3/16X14 in / DCEP	PE8368	Confor	Conforms				orizo	ntal :					Overhead : Conforms									Vertical : Conforms					
5/32X14 in / DCEP	PE8496	Confor	ms			Н	orizo	ntal :		Overh					ead : Conforms					Vertical : Conforms							
							Chen	nical A	nalysi	s																	
Size / Polarity /	Ref. No.	С	Mn	Р	S	Si	Cu	Cr	V	Ni	Мо	AI	Ti	Nb	Co	в١	NS	Sn	Fe	Sb	N	Mg	Zn	Be	Sb	As	
3/16X14 in / DCE	3/16X14 in / DCEP / PE8368		0.45	0.01	0.01	0.11		0.03	0.01	0.56	0.01		Т			Τ											
5/32X14 in / DCEP / PE8496			0.54	0.01	0.01	0.14		0.03	0.01	0.60	0.01		Ť			T	T										

Jenes a Omeng

James A. Owens, Q.A. Specialist

Certification and Limited Warranty - Data for the above supplied product are those obtained when welded and tested in accordance with the above specification. All tests for the above classification were satisfied. Other tests and procedures may produce different results.