

Delivery note no.: 80163820

Customer: Hobart Brothers LLC
1260 Bruckner Drive
Troy, OH 45373

Customer order no.: 2000-002443 / Jon Mi



Quantity delivered: 1,280.00 KG
Customer: (to be filled in by customer)

Type: **FabCOR Matrix**
Diameter Ø: **1.6 mm | 1/16"**
Batch: **A062684**
Specification: **T 46 4 M M21 3 H5**
ISO 17632 A: **E70C-6M H4**
AWS ASME 5.18:

Quantity delivered: (to be filled in by customer)

Current: **±/DCEP** 300 A
Voltage: 30 V
Welding speed: 35 cm/min
Shielding gas / Flux: M21(82/18)
Flow rate: 15 l/min
Stick out: 20 mm
Position: PA (1G)
Interpass temp.: °C 0 °F

Test methods



EN 10204 - 3.1: ISO 6847 All weld metal chemical composition (%)

C	Si	Mn	P	S	Cr	Ni	Mo	Cu	Al	V	Ti	Nb	N2
0,04	0,43	1,22	0,013	0,007	0,026	0,030	0,008	0,011	0,009	0,012	0,031	0,001	0,005
ISO													
		max. 2,00			max. 0,20		max. 0,20						
AWS													
max. 0,12	max. 0,90	max. 1,75	max. 0,03	max. 0,03	max. 0,20	max. 0,50	max. 0,30	max. 0,50		max. 0,08			

EN 10204 - 2.2: Mechanical properties of the pure weld metal (typical values)

Heat-treatment	Tensile test ISO 5178			Impact test ISO 9016 VWT 0/b									
	Rm [MPa]	Rp0,2 [MPa]	A [%]	RT	0°C	-20°C	-40°C	-60°C	RT	32°F	-4°F	-40°F	-76°F
as welded	575	515	25										
	min. 530	min. 460	min. 20										
	83 [ksi]	75 [ksi]	25 [%]			100	60				74	44	
	min. 77	min. 67	min. 20										

Name: Jutzi
Date: 03.08.2022

This document was generated electronically and is valid without signature.