



Certified Material Test Report AWS A5.01 Schedule H, Class S1

Hobart Aluminum · 1631 International Drive · Traverse City, MI 49686

☎ 231-933-1234 📠 231-933-6110 ✉ adam.treon@hobartbrothers.com 🌐 www.hobartbrothers.com

Alloy	Diameter	Package	Lot#
R/ER 4943			36JA20

Lot Chemical Analysis vs. AWS A5.10 Chemistry Classification Designation

	Alloy	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Be	Other		Al
											Each	Total	
AWS (1)	4943	5.0- 6.0	0.40	0.10	0.05	0.10- 0.50	-	0.10	0.15	0.0003	<0.05	<0.15	Rem.
Lot (2) (3)	4943	5.47- 5.53	0.12- 0.14	0.00	0.00	0.38- 0.41	-	0.00	0.02	0.0000	<0.05	<0.15	Rem.

- (1) Single values shown are maximum percentage, except where minimum is specified.
- (2) Certified composition results
- (3) Mercury is not a normal contaminant in aluminum alloys and neither it nor any of its compounds are used in the manufacture of this product.

TYPICAL MECHANICAL PROPERTIES

Mechanical Results		AWS Specification
Tensile	33,700 psi (232 Mpa)	24,000 psi (165 Mpa) Min.
Yield	19,000 psi (131 Mpa)	Not Specified
Elongation	13%	Not Specified

*This typical mechanical information should not be construed as the actual results of this specific lot of material.
No alloy formulation changes since the initiation of this original cert.*

Other customer requirements on sales order: DFARS applies to "specialty metals" and aluminum is not included in the DFARS definition of specialty metals (section 252.225(a)(12)).

Hobart Aluminum hereby certifies that the material covered by this report has been drawn in the USA to the requirements of AWS A5.01, class S1, schedule F & H, controlled chemical composition, and tested in accordance with and been found to meet the requirements of specifications AWS A5.10, ASME/SFA 5.10.



1/15/2026

Adam Treon, Process Quality Systems Manager
Certifying Signature
Hobart Aluminum