

Certificate of Conformance to Requirements for Welding Electrode

Product Type: FabCO 73
Classification: E70T-2

Specifications: AWS A5.20/A5.20M; ASME SFA 5.20

Diameter Tested: 3/32"

Date Tested: 11/21/2022

Date Generated: 11/21/2022

This is to certify that the product named above and supplied on the referenced order number is of the same classification, manufacturing process, and material requirements as the material which was used for the test that was concluded on the date shown, the results of which are shown below. All tests required by the specifications shown for classification were performed at that time and the material tested met all requirements. It was manufactured and supplied by the Quality System Program of Hobart Brothers, which meets the requirements of ISO 9001, ANSI/AWS A5.01, and other specification and Military requirements, as applicable. This document supplies actual test results of non-specific inspection in conformance with the requirements of EN 10204, type 2.2 certification.

THE STEEL USED IN THIS LOT OF MATERIAL WAS MELTED AND MANUFACTURED IN THE U.S.A.

Test Settings

Shielding Medium		Amps / Polarity	Volts	WFS in/min(m/min)	ESC	ESO in(mm)		heat F(C)	Interpass F(C)	Travel Speed in/min(cm/min)	
C1		375 / DCEP	28	150 (3.8)		(25)	Room Temp		300(149)	15 (38.1)	
Mechanical Properties - Tensile											
Shielding Medium		Ref. No.	Testing Conditions		Ult. Tensile Strength psi (MPa)		//Ра)	Yield Strength psi (MPa)		Elong.% in 2"	
C1		pe4896	Aged 48 Hrs 220F		74,000 (511)			NA		NA	
Ref.No.	Ref.No. Radiographic Inspection			Fillet Weld Test							
PE4896	PE4896 None		Horizontal : Confor			ms Overhead :			Vert	ical :	
Longitudinal Bend Test pe4896 :											

James A. Owens, Q.A. Specialist

Certification and Limited Warranty - Data for the above supplied product are those obtained when welded and tested in accordance with the above specification. All tests for the above classification were satisfied. Other tests and procedures may produce different results.