**DOP No. 108** 



## **Declaration of Performance**

In accordance to CPR 305/2011:

1. Identification of product type: Aluminum solid wire electrode

Brand name: Hobart® MaxalMig 5183

Part numbers and diameters: 5183SSSP where S = 030 (0.8 mm), 035 (0.9 mm)

mm), 047 (1.2mm), 062 (1.6mm) and P Package) = 04, 08, 12, 12P, 12P22, 23E, 23L,

23.

Classification: EN ISO 18273 S AI 5183 AIMg4,5Mn0,7(A)

Batch number identifying the Refer

construction product:

Refer to product label

3. Intended use of the construction

product:

Use in metallic structures or composite metal

and concrete structures

4. Name and contact address of

the manufacturer:

Hobart Brothers Co. 1631 International Dr.

Traverse City, MI 49686 USA

5. Authorized representative:

N/A

System 2+

 System of assessment and verification of constancy of performance of the construction

 product:

product:
7. Notified body:

TÜV Rhineland/0035 performed:

- Initial inspection of the manufacturing plant and of factory production control
- Continuous surveillance, assessment, and evaluation of factory production control under System 2+ and issued certificate of conformity of factory production control no. 0035-CPR-C806

8. European Technical

N/A

Assessment:

- 9. Declared performance (see chart on the right):
- 10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer by:

Sail A. Chome

David A. Thomas – Quality Assurance Representative, Traverse City, MI USA 9/14/2015

Essential Characteristics:	Performance:			Harmonized Technical Specification:
	Min	Max	Values	
Chemical composition:				
Si:	-	0.4	%	
Fe:	-	0.4	%	
Cu:	-	0.10	%	
Mn:	0.50	1.0	%	
Mg:	4.3	5.2	%	
Cr:	0.05	0.25	%	EN 13479:2017
Zn:	0.25	0.10	%	
Ga, V:	-	-	%	
Ti:	-	0.15	%	
Zr:	-	-	%	
Al <sub>min:</sub>		Rem	%	
Be:	-	0.0003	%	
Other each:	0.05	0.15	%	
Other total:	0.05	0.15	%	