

Declaration of Performance

In accordance to CPR 305/2011:

1. Identification of product type: Tubular cored electrode welding consumable
 Brand name: Hobart® FabCO® XL-550
 Part numbers and diameters: S245112 (1.2mm), S245115 (1.4mm), S245119 (1.6)
 Classification: EN ISO 17632-A T42 4 P C1 2 H5
 EN ISO 17632-B T49 4 T1-1 C1 AP H5
2. Batch number identifying the construction product: Refer to product label
3. Intended use of the construction product: Metallic structures or composite metal and concrete structures
4. Name and contact address of the manufacturer: Hobart Brothers LLC 101 Trade Square East
Troy, OH 45373 USA
5. Authorized representative: N/A
6. System of assessment and verification of constancy of performance of the construction product: System 2+
7. Notified body/Reg. No: TÜV Rheinland/0035 performed: • Initial inspection of the
 - manufacturing plant and of factory production control
 - Continuous surveillance, assessment, and evaluation of factory production control under System 2+ and issued certificate of conformity of factory production control no. 0035-CPR-C810
8. European Technical Assessment: N/A
9. Declared performance (see chart on the right):
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer by:



James Owens- Compliance Specialist Troy, OH USA 7/15/26

DOP No. 20

Essential Characteristics:	Performance:			Harmonized Technical Specification:
	Min	Max	Values	
Chemical composition:				EN 13479:2017
C:	-	0.18	%	
Mn:	-	2.00	%	
Si:	-	0.90	%	
P:	-	0.030	%	
S:	-	0.030	%	
Cr:	-	0.20	%	
Ni:	-	0.50	%	
Mo:	-	0.2	%	
V:	-	0.08	%	
Nb:	-	0.05	%	
Cu:	-	0.3	%	